

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Revision date: 25/07/2019 Supersedes: 27/02/2018 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Eni i-Sint 5W-30

Product code : 1016

Type of product : Lubricants

Formula : 0187-2019

Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

Industrial/Professional use spec : Used in closed systems

Wide dispersive use: Lubricant for internal combustion engines

Edditodit for little

Do not use the product for any purposes that have not been advised by the manufacturer.

Function or use category : Lubricants and additives

1.2.2. Uses advised against

Use of the substance/mixture

No additional information available

1.3. Details of the supplier of the safety data sheet

ENI S.p.A.

P.le E. Mattei 1 - 00144 Rome Italy

Phone: (+39) 06 59821

www.eni.com

Contact:

Refining & Marketing

Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDSInfo@eni.com

1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)

Poison centre (UK):

National Poisons Information Service Edinburgh (24h)

(+44) 844 892 0111 0870 600 6266 (UK only) (Source: UN-WHO)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

Adverse physicochemical, human health and environmental effects

Contact with eyes may cause temporary reddening and irritation. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

EUH208 - Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

12/09/2019 EN (English) 1/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. In exceptional cases (i.e prolunged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. See Heading 16.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Notes

: Composition/Information on ingredients:

Mixture of hydrocarbons

Polyolefins Additives

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP] |
|--|--|------------|--|
| Distillates (petroleum), hydrotreated heavy paraffinic (see note [**], see note [***]) | (CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25 | 50 - 60 | Asp. Tox. 1, H304 |
| Mineral base oil, severely refined (For identification of the substance, see note [*], see note [***]) | | 10 - 15 | Not classified |
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based, Baseoil - unspecified (see note [**], see note [***]) | (CAS-No.) 72623-86-0 (EC-No.) 276-737-9 (EC Index-No.) 649-482-00-X (REACH-no) 01-2119474878-16 | 1 - 10 | Asp. Tox. 1, H304 |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (see note [**], see note [***]) | (CAS-No.) 72623-87-1 (EC-No.) 276-738-4 (EC Index-No.) 649-483-00-5 (REACH-no) 01-2119474889-13 | 1 - 10 | Asp. Tox. 1, H304 |
| Bis(nonylphenyl)amine | (CAS-No.) 36878-20-3 (EC-No.) 253-249-4 (EC Index-No.) N/A (REACH-no) 01-2119488911-28 | 0,5 - 1,5 | Aquatic Chronic 4, H413 |
| C14-16-18 Alkyl phenol | (EC-No.) 931-468-2 (EC Index-No.) N/A (REACH-no) 01-2119498288-19 | 0,1 - 0,15 | Skin Sens. 1B, H317 STOT RE 2, H373 |

Notes

: [*] Note: this product contains small amounts of severely refined mineral base oil (not classified as hazardous). The identity has not been specified by the original supplier.

This substance has a value < 3 % wt of DMSO extract, according to IP 346/92 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)

Note [**]:

this product has a value of DMSO extract < 3% wt, according to IP 346/92. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Note [***]:

substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.

12/09/2019 EN (English) 2/17

Other information

| Safety Data Sheet | |
|--|---|
| According to Regulation (EU) No. 830/2015 | |
| First-aid measures after skin contact | : Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If inflammation or irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. Do not put ice on the burn. |
| First-aid measures after eye contact | : Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. |
| First-aid measures after ingestion | : Do NOT induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person. |
| 4.2. Most important symptoms and | effects, both acute and delayed |
| Symptoms/effects after inhalation | : This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness. |
| Symptoms/effects after skin contact | Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. Contact with hot product may cause thermal burns. |
| Symptoms/effects after eye contact | : Contact with eyes may cause a light transient irritation. Contact with hot product or vapours may cause burns. |
| Symptoms/effects after ingestion | Accidental ingestion of small quantities of the product may cause irritation, nausea and gastric disturbances. Taking into account the taste of the product, however, ingestion of dangerous quantites is very unlikely. |
| Symptoms/effects upon intravenous administration | : No information available. |
| Chronic symptoms | : None to be reported, according to the present classification criteria. |
| 4.3. Indication of any immediate me | edical attention and special treatment needed |
| | altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of ihalation of H2S (hydrogen sulphide). The casualty should be sent immediately to hospital. Immediately eased. Administer oxygen if necessary. |
| SECTION 5: Firefighting measur | es |
| 5.1. Extinguishing media | |
| Suitable extinguishing media | Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations). |
| Unsuitable extinguishing media | : Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. |
| 5.2. Special hazards arising from the | e substance or mixture |
| Fire hazard | : This product is combustible, but not classied as flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.". |
| Explosion hazard | : Heat may build pressure in tank and containers, rupturing closed vessels, spreading fire and |

| | increasing risk of burns and injuries. In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m³ of air. |
|--|--|
| Hazardous decomposition products in case of fire | : Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NOx, H2S and SOx (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.). POx. ZnOx. |
| 5.3. Advice for firefighters | |
| Firefighting instructions | : Shut off source of product, if possible. If possible, move containers and drums away from danger area. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area. |
| Special protective equipment for firefighters | : Personal protection equipment for firefighters (see also sect. 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659. |

12/09/2019 EN (English) 3/17

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

Safety Data Sheet

According to Regulation (EU) No. 830/2015

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Avoid accidental sprays on hot surfaces or electrical contacts. Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment

: See Section 8.

Emergency procedures

: Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

6.1.2. For emergency responders

Protective equipment

Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

Emergency procedures

: Notify local authorities according to relevant regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.3. Methods and material for containment and cleaning up

For containment

: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.

Other information

Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

12/09/2019 EN (English) 4/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Hygiene measures

: Ensure that proper housekeeping measures are in place. Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store

: Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of

ignition. Do not smoke.

Incompatible products : Keep away from: strong oxidants.

Storage area : Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with

adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.

Packages and containers: : If the product is supplied in containers: Keep containers tightly closed and properly labelled.

Keep only in the original container or in a suitable container for this kind of product.

Packaging materials : For containers, or container linings use materials specifically approved for use with this product.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Distillates (petroleum), | hydrotreated heavy paraffinic (64742-54-7) | |
|--------------------------|--|--|
| Austria | MAK (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Belgium | Limit value (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Denmark | Grænseværdi (langvarig) (mg/m³) | 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Denmark | Grænseværdi (kortvarig) (mg/m³) | 2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Hungary | AK-érték | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Netherlands | MAC TGG 8h (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Spain | VLA-ED (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Spain | VLA-EC (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Sweden | Nivågränsvärde (NVG) (mg/m3) | 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Sweden | Kortidsvärde (KTV) (mg/m3) | 3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| United Kingdom | WEL TWA (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| United Kingdom | WEL STEL (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Canada (Quebec) | VECD (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Canada (Quebec) | VEMP (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - ACGIH | ACGIH TLV®-TWA (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - ACGIH | ACGIH TLV®-STEL (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - NIOSH | NIOSH REL (TWA) (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - NIOSH | NIOSH REL (STEL) (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

12/09/2019 EN (English) 5/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

| " , | , hydrotreated heavy paraffinic (64742-54-7) | |
|-------------------------|--|--|
| USA - OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Mineral base oil, sever | ely refined | |
| Austria | MAK (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Belgium | Limit value (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Denmark | Grænseværdi (langvarig) (mg/m³) | 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Denmark | Grænseværdi (kortvarig) (mg/m³) | 2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Hungary | AK-érték | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Netherlands | MAC TGG 8h (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Spain | VLA-ED (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Spain | VLA-EC (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Sweden | Nivågränsvärde (NVG) (mg/m3) | 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Sweden | Kortidsvärde (KTV) (mg/m3) | 3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| United Kingdom | WEL TWA (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| United Kingdom | WEL STEL (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Canada (Quebec) | VECD (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Canada (Quebec) | VEMP (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - ACGIH | ACGIH TLV®-TWA (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - ACGIH | ACGIH TLV®-STEL (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - NIOSH | NIOSH REL (TWA) (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - NIOSH | NIOSH REL (STEL) (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Lubricating oils (petro | leum), C20-50, hydrotreated neutral oil-based, Bas | seoil - unspecified (72623-87-1) |
| Austria | MAK (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Belgium | Limit value (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Denmark | Grænseværdi (langvarig) (mg/m³) | 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Denmark | Grænseværdi (kortvarig) (mg/m³) | 2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Hungary | AK-érték | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Netherlands | MAC TGG 8h (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Spain | VLA-ED (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Spain | VLA-EC (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Sweden | Nivågränsvärde (NVG) (mg/m3) | 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |

12/09/2019 EN (English) 6/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

| • " | | • | aseoil - unspecified (72623-87-1) |
|----------------------------|------------------------|-----------------------------|--|
| Sweden | Kortidsvärde (K | TV) (mg/m3) | 3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| United Kingdom | WEL TWA (mg/ı | m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| United Kingdom | WEL STEL (mg/ | /m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Canada (Quebec) | VECD (mg/m³) | | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Canada (Quebec) | VEMP (mg/m³) | | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - ACGIH | ACGIH TLV®-T | WA (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - ACGIH | ACGIH TLV®-S | TEL (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - NIOSH | NIOSH REL (TV | VA) (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - NIOSH | NIOSH REL (ST | EL) (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - OSHA | OSHA PEL (TW | 'A) (mg/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Lubricating oils (petrol | eum), C15-30, hydrotre | eated neutral oil-based, Ba | aseoil - unspecified (72623-86-0) |
| Austria | MAK (mg/m³) | , | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Belgium | Limit value (mg/ | m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Denmark | Grænseværdi (la | angvarig) (mg/m³) | 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Denmark | Grænseværdi (k | cortvarig) (mg/m³) | 2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Hungary | AK-érték | | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Netherlands | MAC TGG 8h (n | ng/m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Spain | VLA-ED (mg/m³ |) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Spain | VLA-EC (mg/m³ | , | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Sweden | Nivågränsvärde | (NVG) (mg/m3) | 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Sweden | Kortidsvärde (K | TV) (mg/m3) | 3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| United Kingdom | WEL TWA (mg/ı | m³) | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| United Kingdom | WEL STEL (mg/ | /m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - ACGIH | ACGIH TLV®-T | | 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| USA - ACGIH | ACGIH TLV®-S | TEL (mg/m³) | 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Monitoring methods | | | |
| Monitoring methods | | | ould be chosen according to the indications set by national acts,Refer to relevant legislation and in any case to the good practic |
| Eni i-Sint 5W-30 | | | |
| DNEL/DMEL (additional | information) | | |
| Additional information | | Not applicable | |
| taattoriai iirioirriatiori | | | |
| PNEC (additional informa | ation) | | |
| | ation) | Not applicable | |

12/09/2019 EN (English) 7/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

| Distillates (petroleum), hydrotreated heavy pa | araffinic (64742-54-7) |
|--|--|
| Long-term - systemic effects, inhalation | 5,4 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| DNEL/DMEL (General population) | |
| Long-term - local effects, inhalation | 1,2 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m) |
| Note | The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. |

8.2. Exposure controls

Appropriate engineering controls:

Before entering storage tanks and commencing any operation in a confined area, carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.

Hand protection:

When there is a risk of contact with the skin, use hydrocarbon-resistant, felt-lined gloves. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with filter for hydrocarbon vapours. (EN 136/140/145). Combination filter device (DIN EN 141). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

Personal protective equipment symbol(s):













Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

Environmental exposure controls:

Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Consumer exposure controls:

Wear protective gloves. Avoid excessive or improper use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

12/09/2019 EN (English) 8/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Appearance : Liquid, bright & clear.
Colour : Yellow-brown.

Odour : Slight odour of petroleum.

Odour threshold : There are no data available on the preparation/mixture itself.

pH : Not applicable
Relative evaporation rate (butylacetate=1) : Negligible.

Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Flash point : > 100 °C (ASTM D 92)
Auto-ignition temperature : No data available
Decomposition temperature : No data available

Flammability (solid, gas) : No data available Vapour pressure : No data available Relative vapour density at 20 °C : No data available Relative density : No data available

Solubility : Water: Immiscible and insoluble
Log Pow : Not applicable for mixtures
Viscosity, kinematic : 70 mm²/s (40 °C) (ASTM D 445)

Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

Additional information : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Toxic fumes. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. See also Section 16, "Other information".

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | |
|---|-------------------------|
| LD50 oral rat | > 5000 mg/kg (OECD 401) |
| LD50 dermal rat | > 5000 mg/kg (OECD 402) |
| LC50 inhalation rat (mg/l) | > 5 mg/l/4h (OECD 403) |

12/09/2019 EN (English) 9/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

| According to Regulation (EU) No. 830/2015 | |
|--|--|
| Mineral base oil, severely refined | |
| LD50 oral rat | > 5000 mg/kg bodyweight (OECD 401) |
| LD50 dermal rat | > 5000 mg/kg bodyweight (OECD 402) |
| LC50 inhalation rat (mg/l) | > 5 mg/l/4h (OECD 403) |
| Lubricating oils (petroleum), C20-50, hydrotre | eated neutral oil-based, Baseoil - unspecified (72623-87-1) |
| LD50 oral rat | > 5000 mg/kg (OECD 401) |
| LD50 dermal rat | > 5000 mg/kg (OECD 402) |
| LC50 inhalation rat (mg/l) | > 5 mg/l/4h (OECD 403) |
| (0 / | eated neutral oil-based, Baseoil - unspecified (72623-86-0) |
| LD50 oral rat | 5000 mg/kg (API 1986, UBTL 1983 - OECD 401) |
| LD50 dermal rabbit | 2000 - 5000 mg/kg bodyweight (API 1986, UBTL 1984 - OECD 402) |
| LC50 inhalation rat (mg/l) | 2,18 - 5,53 mg/l/4h (API 1987, Exxon Biomedical Sciences, Inc. 1988, BioResearch |
| LC30 IIIIIaiatioii iat (mg/i) | Laboratories, Ltd. 1984 - OECD 403) |
| Bis(nonylphenyl)amine (36878-20-3) | |
| LD50 oral rat | ≥ 2000 mg/kg bodyweight (OECD 401) |
| | |
| C14-16-18 Alkyl phenol | 2000 m will as heart and table |
| LD50 oral rat | 2000 mg/kg bodyweight |
| LD50 dermal rat | 2000 mg/kg bodyweight |
| Skin corrosion/irritation | : Not classified (Based on available data, the classification criteria are not met) |
| | pH: Not applicable |
| Additional information | : (according to composition) |
| Serious eye damage/irritation | : Not classified (Based on available data, the classification criteria are not met) |
| | pH: Not applicable |
| Additional information | : (according to composition) |
| Respiratory or skin sensitisation | : Not classified (Based on available data, the classification criteria are not met) |
| Additional information | : (according to composition) Contains C14-16-18 Alkyl phenol. Exposure may produce an allergic reaction |
| Germ cell mutagenicity | Not classified (Based on available data, the classification criteria are not met) |
| Additional information | : (according to composition) |
| | |
| Carcinogenicity Additional information | Not classified (Based on available data, the classification criteria are not met) (according to composition) |
| Additional information | This product contains: Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil, and; solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil having a viscosity of approximately 112cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.], Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated hydrocabons.] this product has a value of DMSO extract < 3 % wt, according to IP 346/92. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic. All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346/92 (Nota L - Annex VI Reg (CE) 12 |
| Reproductive toxicity | : Not classified (Based on available data, the classification criteria are not met) |
| Additional information | : (according to composition) |
| | Not classified (Based on available data, the classification criteria are not met)(according to composition) |

12/09/2019 EN (English) 10/17

Safety Data Sheet

ErC50 (algae)

| According | to | Regulation | (FU | No. | 830/2015 |
|-----------|----|------------|-----|-----|----------|
| | | | | | |

| coording to regulation (EO) No. 000/2010 | | | |
|---|--|--|--|
| STOT-repeated exposure | : Not classified (Based on available data, the classification criteria are not met) | | |
| Additional information | : (according to composition) | | |
| Distillates (petroleum), hydrotreated heavy | paraffinic (64742-54-7) | | |
| LOAEL (oral, rat, 90 days) | 125 mg/kg bodyweight/day (OECD TG 408) | | |
| Mineral base oil, severely refined | , | | |
| LOAEL (oral, rat, 90 days) | 125 mg/kg bodyweight/day (OECD TG 408) | | |
| • | reated neutral oil-based, Baseoil - unspecified (72623-87-1) | | |
| LOAEL (oral, rat, 90 days) | 125 mg/kg bodyweight/day (OECD TG 408) | | |
| · · · · · · · · · · · · · · · · · · · | | | |
| | reated neutral oil-based, Baseoil - unspecified (72623-86-0) 125 mg/kg bodyweight/day (Mobil 1990 - OECD TG 408) | | |
| LOAEL (oral, rat, 90 days) LOAEL (dermal, rat/rabbit, 90 days) | 100 mg/kg bodyweight/day (mouse, Chasey, K.L. and McKee, R.H. 1993 - OECD 453) | | |
| NOAEL (dermal, rat/rabbit, 90 days) | 1000 - 2000 mg/kg bodyweight/day (API 1986, Mobil Environmental and Health Science Laboratory 1983 - OECD 410) | | |
| NOAEC (inhalation,rat, vapour, 90 days) | 220 - 1500 mg/m³ (Exxon Biomedical Sciences, Inc. 1991, Dalbey W, Osimitz T, Kommineni C, Roy T, Feuston M and Yang J 1991 - OECD 412) | | |
| C14-16-18 Alkyl phenol | | | |
| NOAEL (oral, rat, 90 days) | 30 - 100 mg/kg bodyweight/day | | |
| Aspiration hazard | : Not classified (Based on available data, the classification criteria are not met) | | |
| Additional information | : Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445) | | |
| Eni i-Sint 5W-30 | | | |
| Viscosity, kinematic | 70 mm ² /s (40 °C) (ASTM D 445) | | |
| Viscosity, Killerhatic | 70 1111175 (40 C) (ASTNI D 443) | | |
| Potential adverse human health effects and symptoms | : Contact with eyes may cause temporary reddening and irritation. Prolonged and repeated skir contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. Avoid all eye and skin contact and do not breathe vapour and mist. | | |
| Other information | : None. | | |
| SECTION 12: Ecological information | | | |
| 12.1. Toxicity | | | |
| Ecology - general | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment. | | |
| Ecology - air | This product has a low vapour pressure. A significant exposure may happen only if the product is used at high temperature, or in case of sprays and mists. | | |
| Ecology - water | : This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment) | | |
| Acute aquatic toxicity | : Not classified (Based on available data, the classification criteria are not met) | | |
| Chronic aquatic toxicity | : Not classified (Based on available data, the classification criteria are not met) | | |
| Distillates (petroleum), hydrotreated heavy | oaraffinic (64742-54-7) | | |
| LC50 fish 1 | > 100 mg/l (LL 50) | | |
| EC50 Daphnia 1 | > 10000 mg/l WAF, 48 h (OECD 202) | | |
| Mineral base oil, severely refined | | | |
| LC50 fish 1 | > 100 mg/l (LL 50) | | |
| EC50 Daphnia 1 | > 10001 mg/(WAF, 48 h (OECD 202) | | |
| · | reated neutral oil-based, Baseoil - unspecified (72623-87-1) | | |
| LC50 fish 1 | > 100 mg/l (LL 50) | | |
| EC50 Daphnia 1 | > 1000 mg/l WAF, 48 h (OECD 202) | | |
| <u> </u> | | | |
| LC50 fish 1 | reated neutral oil-based, Baseoil - unspecified (72623-86-0) > 100 mg/l (LL 50, Exxon 1995 - OECD 203) | | |
| EC50 Daphnia 1 | > 1000 mg/l (LL 50, Exxon 1995 - OECD 203) > 10000 mg/l (WAF, 48 h, Shell 1988 - OECD 202) | | |
| NOEC chronic fish | >= 10000 mg/l (Oncorhynchus mykiss, NOELR, 14d - QSAR, Redman, A. et al. 2010) | | |
| NOEC chronic ristracea | >= 1000 mg/l (21d, OECD 211 - Shell 1994) | | |
| | - 1000 mg/ (E10), OE00 E11 OHOR 100-1 | | |
| Bis(nonylphenyl)amine (36878-20-3) | > 100 mg/l (OECD 203) | | |
| LC50 fish 1 EC50 Daphnia 1 | ≥ 100 mg/l (OECD 203) ≥ 100 mg/l (OECD 202) | | |
| ErC50 (algae) | > 100 mg/l (OECD 202) | | |

12/09/2019 EN (English) 11/17

≥ 100 mg/l (OECD 201; 96h; Scenedesmus capricornutum)

Safety Data Sheet

According to Regulation (EU) No. 830/2015

| C14-16-18 Alkyl phenol | |
|---|--|
| EC50 Daphnia 1 | 100 mg/l |
| | |
| 2.2. Persistence and degradability | |
| Eni i-Sint 5W-30 | |
| Persistence and degradability | The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. |
| Distillates (petroleum), hydrotreated heavy p | araffinic (64742-54-7) |
| Persistence and degradability | The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. |
| Mineral base oil, severely refined | |
| Persistence and degradability | The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. |
| Lubricating oils (petroleum), C20-50, hydrotro | eated neutral oil-based, Baseoil - unspecified (72623-87-1) |
| Persistence and degradability | The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. |
| Lubricating oils (petroleum), C15-30, hydrotro | eated neutral oil-based, Baseoil - unspecified (72623-86-0) |
| Persistence and degradability | The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions. |
| Bis(nonylphenyl)amine (36878-20-3) | |
| Persistence and degradability | Not biodegradable. |
| C14-16-18 Alkyl phenol | |
| Biodegradation | 24 % (Zahn-Wellens, 10-20 %) |
| 2.3. Bioaccumulative potential | |
| Eni i-Sint 5W-30 | |
| Log Pow | Not applicable for mixtures |
| Bioaccumulative potential | Not established. |
| · | eated neutral oil-based, Baseoil - unspecified (72623-86-0) |
| Bioaccumulative potential | The test methods for this endpoint are not applicable to UVCB substances. |
| C14-16-18 Alkyl phenol | |
| Log Kow | 4,5 (0.1 d, 10-20 %) |
| | +,5 (0.1 d, 10 20 70) |
| 2.4. Mobility in soil | |
| Eni i-Sint 5W-30 | No data confloida |
| Ecology - soil | No data available. |
| | eated neutral oil-based, Baseoil - unspecified (72623-86-0) |
| Ecology - soil | The test methods for this endpoint are not applicable to UVCB substances. |
| 2.5. Results of PBT and vPvB assessmen | ıt erine |
| Eni i-Sint 5W-30 | |
| This substance/mixture does not meet the PBT | |
| This substance/mixture does not meet the vPvB | |
| Results of PBT-vPvB assessment | The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Component | |
| Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Mineral base oil, severely refined () | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |

12/09/2019 EN (English) 12/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

| Component | |
|--|--|
| Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, Baseoil - unspecified (72623-86-0) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1) | This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1) |

12.6. Other adverse effects

Other adverse effects : None.

Additional information : This product has no specific properties for inhibition of bacterial activity. In any case,

wastewater containing this product should be treated in plants that are suited for the specific purpose.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.

Sewage disposal recommendations : Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or

reclaimed. Dispose of in a safe manner in accordance with local/national regulations.

Product/Packaging disposal recommendations : European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has

the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.

Additional information : Empty containers may contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been cleaned, and declared safe.

Ecology - waste materials : The product as it is does not contain halogenated substances.

EURAL code (EWC) : 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADN / ADR / IATA / IMDG / RID

| ADR | IMDG | IATA | ADN | RID |
|-----------------------------|----------------------------------|---------------|---------------|---------------|
| 14.1. UN number | | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.2. UN proper shippi | ng name | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.3. Transport hazard | 14.3. Transport hazard class(es) | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.4. Packing group | 14.4. Packing group | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |
| 14.5. Environmental hazards | | | | |
| Not regulated | Not regulated | Not regulated | Not regulated | Not regulated |
| None. | | | | |

14.6. Special precautions for user

- Overland transport

Not regulated

- Transport by sea

Not regulated

- Air transport

Not regulated

- Inland waterway transport

Not regulated

- Rail transport

Not regulated

12/09/2019 EN (English) 13/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

| 3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10 | Distillates (petroleum), hydrotreated heavy paraffinic - C14-16-18 Alkyl phenol - Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, Baseoil - unspecified - Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified |
|--|---|
| 3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1 | Bis(nonylphenyl)amine |

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

Contains no REACH Annex XIV substances

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et seguens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) -Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directives 75/439/CEE - 87/101/CEE concerning disposal of used oils.

France

Maladies professionelles (F) : RG 36 - Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse

Germany

Reference to AwSV : Water hazard class (WGK) (D) 1, Slightly hazardous to water (Classification according to

AwSV, Annex 1)

WGK remark : Classification based on the components in compliance with Verwaltungsvorschrift

wassergefährdender Stoffe (VwVwS)

VbF class (D) : Not applicable.

Storage class (LGK) (D) : LGK 10 - Combustible liquids

: Employment prohibitions or restrictions on the protection of young people at work according to

§ 22 JArbSchG in the case of formation of hazardous substances have to be observed.

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV

Employment restrictions

Other information, restrictions and prohibition regulations

: TRGS 400: Hazard assessment for activities involving Hazardous Substances

TRGS 401: Risks resulting from skin contact - identification, assessment, measures

TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous

Substances: Inhalation Exposure TRGS 500: Protective measures

TRGS 555: Working instruction and information for workers

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

TRGS 900: Occupational Exposure Limits TRGS 800: Fire protection measures

12/09/2019 EN (English) 14/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

Netherlands

Saneringsinspanningen : C - Minimize discharge

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen - Borstvoeding

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen - Vruchtbaarheid

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting

: None of the components are listed

giftige stoffen - Ontwikkeling

Denmark

Danish National Regulations

: Young people under 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with it

15.2. **Chemical safety assessment**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP] No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture:

Distillates (petroleum), hydrotreated heavy paraffinic

Changed Hans

C14-16-18 Alkyl phenol

Bis(nonylphenyl)amine

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based, Baseoil - unspecified Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified

SECTION 16: Other information

Indication of changes:

| Section | Changed item | Change | Notes |
|---------|---|----------|-------|
| 1.1 | Formula | Modified | |
| 2.1 | Adverse physicochemical, human health and environmental effects | Modified | |
| 2.2 | No labelling obligation | Removed | |
| 2.2 | EUH-statements | Added | |
| 2.3 | Other hazards not contributing to the classification | Modified | |
| 3 | Composition/information on ingredients | Modified | |
| 3.2 | Comments | Added | |
| 3.2 | Notes | Added | |
| 4.1 | First-aid measures after ingestion | Modified | |
| 4.2 | Symptoms/effects after skin contact | Modified | |
| 5.2 | Explosion hazard | Modified | |
| 5.2 | Hazardous decomposition products in case of fire | Added | |
| 7.1 | Hygiene measures | Modified | |
| 7.1 | Precautions for safe handling | Modified | |
| 8.2 | Consumer exposure controls | Modified | |
| 8.2 | Hand protection | Modified | |
| 9.1 | Melting point | Removed | |
| 9.1 | Viscosity, kinematic | Modified | |
| 9.1 | Flash point | Modified | |
| 9.1 | Density | Removed | |
| 10.4 | Conditions to avoid | Modified | |
| 11.1 | Additional information | Modified | |
| 11.1 | Additional information | Modified | |
| 11.1 | Potential adverse human health effects and symptoms | Modified | |
| 14.6 | Special transport precautions | Removed | |
| 15.1 | Other information, restrictions and prohibition regulations | Modified | |
| 15.1 | Storage class (LGK) (D) | Modified | |
| 15.1 | REACH Annex XVII | Modified | |

12/09/2019 EN (English) 15/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

| 15.1 | Other information, restriction and prohibition regulations | Added | |
|------|--|----------|--|
| 16 | Abbreviations and acronyms | Modified | |
| 16 | Indication of changes | Added | |

Abbreviations and acronyms:

| | Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product. |
|-------|---|
| | N/A = not applicable |
| | N/D = not available |
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| CLP | Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 |
| DMEL | Derived Minimal Effect level |
| DNEL | Derived-No Effect Level |
| EC50 | Effective concentration for 50 percent of test population (median effective concentration) |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Lethal concentration for 50 percent of test population (median lethal concentration) |
| LD50 | Lethal dose for 50 percent of test population (median lethal dose) |
| LOAEL | Lowest Observed Adverse Effect Level |
| NOAEC | No-Observed Adverse Effect Concentration |
| NOAEL | No-Observed Adverse Effect Level |
| NOEC | No-Observed Effect Concentration |
| OECD | Organisation for Economic Co-operation and Development |
| PBT | Persistent Bioaccumulative Toxic |
| PNEC | Predicted No-Effect Concentration |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006 |
| RID | Regulation concerning the International Carriage of Dangerous Goods by Railways |
| SDS | Safety Data Sheet |
| STP | Sewage treatment plant |
| vPvB | Very Persistent and Very Bioaccumulative |

Data sources

Training advice

Other information

- : This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
- : Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
- : Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolunged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H2S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

Full text of H- and EUH-statements:

| Tuil text of 11- and Lot 1-statements. | | |
|--|--|--|
| Aquatic Chronic 4 | Hazardous to the aquatic environment — Chronic Hazard, Category 4 | |
| Asp. Tox. 1 | Aspiration hazard, Category 1 | |
| Skin Sens. 1B | Skin sensitisation, category 1B | |
| STOT RE 2 | Specific target organ toxicity — Repeated exposure, Category 2 | |
| H304 | May be fatal if swallowed and enters airways. | |
| H317 | May cause an allergic skin reaction. | |
| H373 | May cause damage to organs through prolonged or repeated exposure. | |
| H413 | May cause long lasting harmful effects to aquatic life. | |
| EUH208 | Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. | |
| EUH210 | Safety data sheet available on request. | |

12/09/2019 EN (English) 16/17

Safety Data Sheet

According to Regulation (EU) No. 830/2015

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

12/09/2019 EN (English) 17/17