

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 21/09/2022 Supersedes: 19/07/2022 Version: 8.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Product form : Mixture : Eni Rotra ATF III Trade name Product code : 1298 Lubricants Type of product ÷ Formula : 0190-2020 Product group : Trade product 1.2. Relevant identified uses of the substance or mixture and uses advised against 1.2.1. Relevant identified uses Main use category : Industrial use, Professional use, Consumer use Industrial/Professional use spec Used in closed systems Wide dispersive use : Gearbox lubricant Use of the substance/mixture Do not use the product for any purposes that have not been advised by the manufacturer. Function or use category : Lubricants and additives 1.2.2. Uses advised against No additional information available

1.3. Details of the supplier of the safety data sheet

ENI S.p.A. P.le E. Mattei 1 - 00144 Rome Italy Phone: (+39) 06 59821 www.eni.com

Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDSInfo@eni.com

1.4. Emergency telephone number	
Emergency number	: CNIT +39 0382 24444 (24h) (IT + EN)
	Poison centre (UK): National Poisons Information Service Edinburgh (24h) (+44) 844 892 0111 0870 600 6266 (UK only) (Source: UN-WHO)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412 Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects

Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May cause an allergic skin reaction. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2.2. Label elements		
Labelling according to Regulation (EC) No. 1272/2008 [CLP]		
CLP Signal word	: -	
Hazard statements (CLP)	: H412 - Harmful to aquatic life with long lasting effects.	
Precautionary statements (CLP)	: P273 - Avoid release to the environment.	
EUH-statements	 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. EUH208 - Contains 1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives. May produce ar 	
	allergic reaction.	
2.3. Other hazards (not relevant for classif	ication)	
Other hazards not contributing to the classification	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of contact with eyes, this product may cause irritation. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. In exceptional cases (i.e prolunged storage	

victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. In exceptional cases (i.e prolunged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness, loss of consciousness and death.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Component		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Mineral base oil, severely refined (N/A)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component	
Distillates (petroleum), hydrotreated heavy paraffinic(64742-54-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
Distillates (petroleum), solvent-refined light paraffinic(64741-89-5)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
Distillates (petroleum), hydrotreated heavy paraffinic(64742-54-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
Mineral base oil, severely refined(N/A)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Notes

: Composition/ Information on ingredients: Mixture of hydrocarbons Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (see note [**], see note [***]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	60 - 70	Asp. Tox. 1, H304
Distillates (petroleum), solvent-refined light paraffinic (see note [**], see note [***]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	(CAS-No.) 64741-89-5 (EC-No.) 265-091-3 (EC Index-No.) 649-455-00-2 (REACH-no) 01-2119487067-30	20 - 30	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	(CAS-No.) 64742-54-7 (EC-No.) 265-157-1 (EC Index-No.) 649-467-00-8 (REACH-no) 01-2119484627-25	20 – 25	Not classified
Distillates (petroleum) hydrotreated light paraffinic (see note [**], see note [***]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	(CAS-No.) 64742-55-8 (EC-No.) 265-158-7 (EC Index-No.) 649-468-00-3 (REACH-no) 01-2119487077-29	1 - 5	Asp. Tox. 1, H304

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Mineral base oil, severely refined (For identification of the substance, see note [*], see note [***]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	(CAS-No.) N/A (EC-No.) N/A	0,5 - 1,5	Asp. Tox. 1, H304
1-(tert-dodecylthio)propan-2-ol (Additive)	(CAS-No.) 67124-09-8 (EC-No.) 266-582-5 (EC Index-No.) N/A (REACH-no) 01-2119953277-30	0,1 - 0,9	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives (Additive)	(EC-No.) 482-000-4 (EC Index-No.) N/A (REACH-no) 01-0000020142-86	0,1 - 0,5	Skin Sens. 1, H317 Aquatic Chronic 3, H412
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (Additive)	(CAS-No.) 1218787-32-6 (EC-No.) 620-540-6 (EC Index-No.) N/A (REACH-no) 01-2119510877-33	< 0,1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
1-(tert-dodecylthio)propan-2-ol (Additive)	(CAS-No.) 67124-09-8 (EC-No.) 266-582-5 (EC Index-No.) N/A (REACH-no) 01-2119953277-30	(14,2 ≤C < 100) Skin Sens. 1, H317

Notes

[*] Note: this product may be formulated with one or more of the following severely refined mineral base oils (not classified as hazardous):
CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-65-0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-4/REACH Reg. # 01-2119487080-42-xxxx.
All these substances have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)
Note [**]:
this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.
Note [***]:
substance with occupational exposure limits for some EU countries affecting the category of

mineral oils (finely refined mineral base oil mists; see section 8.1)

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.
First-aid measures after skin contact	: Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If inflammation or irritation persists, seek medical advice. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. Body hypothermia must be avoided. Do not put ice on the burn.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

First-aid measures after eye contact First-aid measures after ingestion	 Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to an hospital. Do not use salves or ointments, unless directed by doctor. Do NOT induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.
4.2. Most important symptoms and effects,	both acute and delayed
Symptoms / injuries (general indications) Symptoms/effects after inhalation	 Not expected to present a significant hazard under anticipated conditions of normal use. This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness.
Symptoms/effects after skin contact	: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. Contact with hot product may cause thermal burns.
Symptoms/effects after eye contact	: Contact with eyes may cause temporary reddening and irritation. Contact with hot product or vapours may cause burns.
Symptoms/effects after ingestion	: Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances.
Symptoms/effects upon intravenous administration	: No information available.
Chronic symptoms	: None to be reported, according to the present classification criteria.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	 Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations). Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. 	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m3 of air. Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NOx, H2S and SOx (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.). POx. 	
5.3. Advice for firefighters		
Firefighting instructions	: Shut off source of product, if possible. Move undamaged containers from immediate hazard area if it can be done safely. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Special protective equipment for firefighters	: Personal protection equipment for firefighters (see also sect. 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.
Other information	: In case of fire, do not discharge residual product, waste materials and runoff water: collect
	separately and use a proper treatment.

SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures General measures : Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material. Keep upwind. 6.1.1. For non-emergency personnel Protective equipment : See Section 8. Emergency procedures : Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency. 6.1.2. For emergency responders Protective equipment Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heatresistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used. Emergency procedures : Notify local authorities according to relevant regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

	· Contain anillad liquid with and, anther ather suitable shouth atta (any flowmable)
For containment	: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable).
	Recover free liquid and waste materials in suitable waterproof and oil-resistant containers.
	Clean contaminated area. Dispose of according to local regulations. If in water: Confine the
	spillage. Remove from surface by skimming or suitable floating absorbents. Collect
	recovered product and other waste materials in suitable waterproof, oil resistant containers.
	Recover or dispose of according to local regulations. Do not use solvents or dispersants,
	unless specifically advised by an expert, and, if required, approved by local authorities.
Other information	: Recommended measures are based on the most likely spillage scenarios for this material;
	however, local conditions (wind, air/water temperature, wave/current direction and speed)
	may significantly influence the choice of appropriate actions. Local regulations may also
	prescribe or limit actions to be taken. For this reason, local experts should be consulted
	when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 7: Handling and storage

Precautions for safe handling	: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".
Handling temperature	: This product can be handled at ambient temperatures.
Hygiene measures	: Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.
7.2. Conditions for safe storage, inclu	iding any incompatibilities
Storage conditions	: Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
Incompatible products	: Keep away from: strong oxidants.
Storage temperature	: This product can be stored at ambient temperatures.
Storage area	 Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
Packages and containers:	: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
	: For containers, or container linings use materials specifically approved for use with this

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA 5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		

Safety Data Sheet

Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH OEL STEL	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)		
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Mineral base oil, severely refined (N/A)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KTV (OEL STEL)	3 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.1.2. Recommended monitoring procedures

Monitoring methods	
5	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

8.1.3. Air contaminants formed

No additional information available

Eni Rotra ATF III		
DNEL/DMEL (additional information)		
Additional information	Not applicable	
PNEC (additional information)		
Additional information	Not applicable	

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,7 mg/m³	
Long-term - local effects, inhalation	5,6 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1,2 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
PNEC (Oral)		
PNEC oral (secondary poisoning)	9,33 mg/kg food	

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,73 mg/m ³	
Long-term - local effects, inhalation	5,58 mg/m ³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1,19 mg/m³	
PNEC (Oral)		
PNEC oral (secondary poisoning)	9,33 mg/kg food	

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,73 mg/m³
Long-term - local effects, inhalation	5,58 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral 0,74 mg/kg bodyweight/day	

Safety Data Sheet

Long-term - local effects, inhalation	1,19 mg/m³
PNEC (Oral)	
PNEC oral (secondary poisoning)	9,33 mg/kg food

1-(tert-dodecylthio)propan-2-ol (67124-09-8)		
DNEL/DMEL (Workers)		
Acute - local effects, dermal	0,2154 mg/cm ²	
Long-term - systemic effects, dermal	3,34 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	11,8 mg/m ³	
DNEL/DMEL (General population)		
Acute - local effects, dermal	0,1077 mg/cm²	
Long-term - systemic effects,oral	0,84 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,9 mg/m ³	
Long-term - systemic effects, dermal	1,67 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	6,4 μg/l	
PNEC aqua (marine water)	0,64 µg/l	
PNEC aqua (intermittent, freshwater)	5,8 μg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	8,28 mg/kg dwt	
PNEC sediment (marine water)	0,828 mg/kg dwt	
PNEC (Soil)		
PNEC soil	244 µg/kg	
PNEC (Oral)		
PNEC oral (secondary poisoning)	33,33 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	

1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives		
DNEL/DMEL (additional information)		
Additional information	not derived	
PNEC (additional information)		
Additional information	Not yet determined.	

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0,3 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2,112 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0,214 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	745 µg/m³	
Long-term - systemic effects, dermal	0,214 mg/kg bodyweight/day	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

PNEC (Water)		
PNEC aqua (freshwater)	214 ng/l	
PNEC aqua (marine water)	21,4 ng/l	
PNEC aqua (intermittent, freshwater)	0,87 µg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	1,692 mg/kg dwt	
PNEC sediment (marine water)	169,2 µg/kg dw	
PNEC (Soil)		
PNEC soil	5 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	2 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	1,5 mg/l	

```
Note
```

: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limit (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure that there is a suitable ventilation system. Before entering storage tanks and commencing any operation in a confined area, carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

8.2.2. Personal protection equipment

Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

8.2.2.2. Skin protection

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Hand protection:

When there is a risk of contact with the skin, use hydrocarbon-resistant, felt-lined gloves. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

8.2.2.3. Respiratory protection

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with filter for hydrocarbon vapours. (EN 136/140/145). Combined gas/dust mask with filter type: EN 14387. Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

8.2.2.4. Thermal hazards

Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Prevent discharge of undissolved substance to or recover from onsite wastewater. Onsite wastewater treatment required. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Consumer exposure controls:

Wear protective gloves. Ensure adequate ventilation.

SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties		
Odour threshold Melting point Freezing point	 Shight oddu of perforeant. There are no data available on the preparation/mixture itself. Not determined -60 – 0 °C (CAS 64742-54-7) 	
Boiling point Flammability Explosive properties	 : ≥ 200 (ASTM D 1160) : Not flammable : None (according to composition). 	
Oxidising properties Explosive limits Lower explosive limit (LEL) Upper explosive limit (UEL)	 None (according to composition). ≥ 45 g/m³ (Aerosol) Not determined Not determined 	
Flash point Auto-ignition temperature Decomposition temperature	 Not determined ≥ 180 °C (ASTM D 92) > 300 °C (CAS 64742-54-7) Not determined 	
pH Viscosity, kinematic	: Not available : 32,5 mm²/s (40 °C) (ASTM D 445)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Solubility	: Water: Immiscible and insoluble
Log Kow	: Not applicable for mixtures
Log Pow	: Not applicable for mixtures
Vapour pressure	: ≤ 0,1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)
Vapour pressure at 50 °C	: Not determined
Critical pressure	: Not applicable for mixtures
Density	: Not determined
Relative density	: Not determined
Relative vapour density at 20 °C	: Not determined
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable
9.2 Other information	

9.2. Other information

9.2.1. Information with regard to physical h	azard classes
Critical temperature	: Not applicable for mixtures
9.2.2. Other safety characteristics	
Relative evaporation rate (butylacetate=1) Additional information	: Negligible. : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : Toxic fumes. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. See also Section 16, "Other information".

SECTION 11: Toxicological information	
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008	
Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) Acute toxicity (inhalation)	 Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)

Safety Data Sheet

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
> 5000 mg/kg (OECD 401)	
> 5000 mg/kg (OECD 402)	
> 5 mg/l/4h (OECD 403)	
I	

Distillates (petroleum), solvent-refined light pa	araffinic (64741-89-5)
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LD50 dermal rabbit	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	> 5,53 mg/l/4h (EBSI, 1988)

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)

Mineral base oil, severely refined (N/A)	
LD50 oral rat	≥ 5000 mg/kg bodyweight (OECD 401)
LD50 dermal rat	≥ 5000 mg/kg bodyweight (OECD 402)

1-(tert-dodecylthio)propan-2-ol (67124-09-8)	
LD50 oral rat	5000 mg/kg bodyweight
LD50 dermal rabbit	2000 mg/kg bodyweight

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)	
LD50 oral rat	1200 – 2000 mg/kg bodyweight
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Additional information Serious eye damage/irritation	 (according to composition) Not classified (Based on available data, the classification criteria are not met)
Additional information Respiratory or skin sensitisation	 (according to composition) Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition) Contains 1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives.
Germ cell mutagenicity	Exposure may produce an allergic reaction : Not classified (Based on available data, the classification criteria are not met)
Additional information Carcinogenicity	 : (according to composition) : Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

Additional information :	(according to composition) This product contains : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Distillates (petroleum), solvent-refined light paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).], Distillates (petroleum), hydrotreated light paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic. All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3) No carcinogenic effect
Reproductive toxicity:Additional information:	Not classified (Based on available data, the classification criteria are not met) (according to composition)
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight
STOT-single exposure : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)
2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)
NOAEL (acute, oral, animal/male)	13 mg/kg bodyweight
STOT-repeated exposure : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)
Distillatos (notroloum), hydrotroatod hoavy na	roffinic (64742.54.7)

1		
	LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
Distillates (petroleum), hydrotreated neavy paraminic (64742-54-7)		raminic (64742-54-7)

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)

Mineral base oil, severely refined (N/A)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
Aspiration hazard :	Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Additional information	: (according to composition) Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445)
Eni Rotra ATF III	
Viscosity, kinematic	32,5 mm²/s (40 °C) (ASTM D 445)
11.2. Information on other hazards	
11.2.1. Endocrine disrupting properties	
Adverse health effects caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
11.2.2 Other information	
Potential adverse human health effects and symptoms	: Contact with eyes may cause temporary reddening and irritation, Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, May produce an allergic reaction, Avoid all eye and skin contact and do not breathe vapour and mist
Other information	: None

SECTION 12: Ecological information

12.1. Toxicity	
Ecology - general	: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. An uncontrolled release to the environment may produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment. Notify authorities if product enters sewers or public waters.
Ecology - air	: This product has a low vapour pressure. A significant exposure may happen only if the product is used at high temperature, or in case of sprays and mists.
Ecology - water	: This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)
Ecology - water	: Harmful to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	
LC50 fish 1	100 – 10000 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

EC50 72h - Algae [1]	100 mg/l (EL0, Pseudokirchneriella subcapitata)
NOEC (chronic)	10 – 1000 mg/l (NOELR, Daphnia Magna)
NOEC chronic algae	100 mg/l (72h, Pseudokirchneriella subcapitata)

Mineral base oil, severely refined (N/A)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

1-(tert-dodecylthio)propan-2-ol (67124-09-8)	
LC50 fish 1	750 μg/l
EC50 Daphnia 1	580 μg/l
EC50 96h - Algae [1]	> 100 mg/l

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol (1218787-32-6)	
LC50 fish 1	0,1 mg/l (Brachydanio rerio)
EC50 Daphnia 1	0,043 mg/l (Daphnia Magna)
EC50 72h - Algae [1]	0,0538 mg/l (Pseudokirchneriella subcapitata)
NOEC chronic algae	0,0158 mg/l (Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

Eni Rotra ATF III	
	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
Biodegradation	31 % (28d, Exxon 1995)

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
Biodegradation	< 60 % (28d)

Safety Data Sheet

Mineral base oil, severely refined (N/A)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
1-(tert-dodecylthio)propan-2-ol (67124-09-8)		
Biodegradation	5,9 % (28d, OECD TG 301 F)	
2,2'-(C16-18 (evennumbered, C18 unsaturated	() alkyl imino) diethanol (1218787-32-6)	
Biodegradation	63 % (28 d, OECD TG 301 D)	
12.3. Bioaccumulative potential		
Eni Rotra ATF III		
Log Pow	Not applicable for mixtures	
Log Kow	Not applicable for mixtures	
Bioaccumulative potential	Not established.	
Distillates (petroleum), solvent-refined light p		
Bioaccumulative potential	The test methods for this endpoint are not applicable to UVCB substances.	
Distillates (petroleum) hydrotreated light para	affinic (64742-55-8)	
Log Kow	< 1	
1-(tert-dodecylthio)propan-2-ol (67124-09-8)		
Log Kow	5,7	
2,2'-(C16-18 (evennumbered, C18 unsaturated		
Bioconcentration factor (BCF REACH)	110,2	
Log Kow	3,6	
12.4. Mobility in soil		
Eni Rotra ATF III		
Mobility in soil	Not determined	
Ecology - soil	No data available.	
Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
Ecology - soil	This product is not soluble in water. It floats on water and forms a film on the surface.	
12.5. Results of PBT and vPvB assessment	·	
Eni Rotra ATF III		
This substance/mixture does not meet the PBT criteria	of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria	a of REACH regulation, annex XIII	
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Mineral base oil, severely refined (N/A)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
12.6. Endocrine disrupting properties	·
Adverse effects on the environment caused by endocrine disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified a having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
12.7. Other adverse effects	
Other adverse effects Additional information	 None This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector. Dispose of empty containers and wastes safely.	
Sewage disposal recommendations	: Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Product/Packaging disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.	
Additional information	: Empty containers may contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been cleaned, and declared safe.	
Ecology - waste materials	: The product as it is does not contain halogenated substances.	
EURAL code (EWC)	: 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils	

purpose.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

In accordance with ADR / IM	DG / IATA / ADN / RID			
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID n	umber			
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shippin	g name			
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

14.6. Special precautions for user

Overland transport Not regulated Transport by sea Not regulated Air transport Not regulated Inland waterway transport Not regulated Rail transport Not regulated

14.7. Maritime transport in bulk according to IMO instruments

IBC code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
3(c)	1-(tert-dodecylthio)propan-2-ol ; 1,2- Propanediol, 3-amino-, N,N dicocoalkyl derivatives ; 2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
3(b)	Distillates (petroleum), hydrotreated heavy paraffinic ; Distillates (petroleum), solvent- refined light paraffinic ; 1-(tert- dodecylthio)propan-2-ol ; 1,2-Propanediol, 3- amino-, N,N dicocoalkyl derivatives ; Mineral base oil, severely refined ; 2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol ; Distillates (petroleum) hydrotreated light paraffinic	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC). Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants.

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE). Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

France

Maladies profession		
Code	Description	
RG 36	Diseases caused by oils and fats of mineral or synthetic origin	
Germany		
Employment restrictio	ns	: Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.
Water hazard class (V	VGK) (D)	: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)
WGK remark		: Classification is carried out on the basis of the Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV)) of 18 April 2017 (BGBI 2017, Teil I, Nr. 22, Seite 905).
	ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
National Rules and R	ecommendations	 TRGS 400: Hazard assessment for activities involving Hazardous Substances TRGS 401: Risks resulting from skin contact - identification, assessment, measures TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure TRGS 500: Protective measures TRGS 555: Working instruction and information for workers TRGS 800: Fire protection measures TRGS 900: Occupational Exposure Limits TRGS 905: List of mutagenic, carcinogenic or teratogenic substances
Storage class (LGK, 1	FRGS 510)	: LGK 10 - Combustible liquids
VbF class (D)		: Not applicable.
Netherlands		
Waterbezwaarlijkheid		 8 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment 9 - Harmful to aquatic organisms
Saneringsinspanninge	en	: C - Minimize discharge

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen –	: None of the components are listed
Vruchtbaarheid	
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed
Denmark	
Danish National Regulations	: Young people under 18 years are not allowed to use the product
	Pregnant/breastfeeding women working with the product must not be in direct contact with it
Switzerland	
Storage class (LK)	: LK 10/12 - Liquids
15.2. Chemical safety assessment	

For this mixture a chemical safety assessment has been not carried out

A chemical safety assessment has been carried out for the following components of this mixture:

Distillates (petroleum), hydrotreated heavy paraffinic

Distillates (petroleum), solvent-refined light paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives

2,2'-(C16-18 (evennumbered, C18 unsaturated) alkyl imino) diethanol

Distillates (petroleum) hydrotreated light paraffinic

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Notes
2	Hazard statements (CLP)	Modified	
3.2	Composition/information on ingredients	Modified	

Abbreviations and acronyms:			
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.N/D = not available		
	N/A = not applicable		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC50	Effective concentration for 50 percent of test population (median effective concentration)		
IARC	International Agency for Research on Cancer		
ΙΑΤΑ	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)		
LD50	Lethal dose for 50 percent of test population (median lethal dose)		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
РВТ	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006		
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
vPvB	Very Persistent and Very Bioaccumulative		
Data sources	: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking		

Training advice

Other information

into account the information provided by the suppliers.Provide adequate training to professional operators for the use of PPEs, according to the information

Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.

: Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolunged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H2S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. Therefore, it is very important to follow the above mentioned precautionary measures also with used oils.

Full text of H- and EUH-statements:			
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Asp. Tox. 1	Aspiration hazard, Category 1		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C		
Skin Sens. 1	Skin sensitisation, Category 1		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H314	Causes severe skin burns and eye damage.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

H412 Ha	Harmful to aquatic life with long lasting effects.	
EUH208 Contains 1,2-Propanediol, 3-amino-, N,N dicocoalkyl derivatives. May produce an aller		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.